

# URINALS

## Siphonic urinal VILA 84114.1



### TECHNICAL DATA

Order no.	84114.1
Certified to	EN 13407
matching for	LIS CU2 Concealed frame for urinal without integrated control, order no. 89266.4 LIS SMART CONTROL-U, order no. 37066.0
Specification	1-l flushing siphonic urinal Only to be used with cover only in combination with fixing set order no. 89280.8
Water inlet	concealed
Outlet	horizontal
Flushing	1 l
Flushing rate	minimum 0.3 l/s
Weight	20,0 kg
Accessories excl.	Urinal cover, order no. 89414.2
Mounting acc. incl.	Wall fixing set M8 LAUFEN, order no. 89280.8
Mounting acc. excl.	LIS CU2 horizontal inlet connection, order no. 89900.7 LIS SMART CONTROL-U horizontal inlet connection, order no. 89418.9 1-litre siphon with horizontal outlet DN 50 (standard Europe, except CH and UK), order no. 89418.1

Mounting acc. excl.	2-litre siphon with horizontal outlet DN 40 (standard UK), order no. 89418.3 Stone screw fixing set M8 Adaption set for stone screws M10, order no. 89281.6 Adaption set for stone screws M12, order no. 89281.4
---------------------	--

Colours see colour table

### SPECIFICATION TEXT

Siphonic urinal Laufen-VILA, sanitary ceramic EN 13407, dimensions 310 x 280 x 490 mm only to be used with cover  
1-l flush, water inlet concealed, outlet horizontal, flushing rate minimum 0.3 l/s  
Special feature: Vacuum and performance tested  
Further options / accessories: Surface refinement LCC (only white), LIS horizontal inlet connection, 1-litre siphon with horizontal outlet DN 50 (standard Europe, except CH and UK), 2-litre siphon with horizontal outlet DN 40 (standard UK), urinal cover, LIS CU2 concealed frame for urinal without integrated control or LIS SMART CONTROL-U concealed kit for urinal flush control and front plate with infrared sensor  
Order no. 84114.1

### TECHNICAL DRAWINGS / S 1 : 20

