

URINALS

Siphonic urinal TARO-UNI 84000.5



TECHNICAL DATA

Order no.	84000.5
Certified to	DIN 1390
Water inlet	external
Outlet	horizontal or vertical
Flushing quantity	minimum 1 l
Flushing capacity	minimum 0.3 l/s
Weight	20,0 kg
Mounting acc. excl.	vertical inlet connection, order no. 89900.7 all siphons has to be used in combination with the outlet connection pipe (order no. 89397.3) 1-litre siphon with horizontal outlet DN 50 (standard Europe, except CH and UK), order no. 89418.1 1-litre siphon with horizontal and vertical outlet DN 50 SH 50 (standard Europe, except CH and UK), order no. 89583.9

Mounting acc. excl.	1-litre siphon with horizontal and vertical outlet DN 40 SH 50 (standard CH), order no. 89584.0 Stone screws, order no. 89406.0
Colours	see colour table

SPECIFICATION TEXT

Siphonic urinal Laufen-TARO-UNI, sanitary ceramic
DIN 1390, dimensions 390 x 390 x 745 mm

minimum 1-l flush, water inlet external, outlet horizontal or vertical, flushing rate minimum 0.3 l/s

Special feature: Vacuum and performance tested

Further options / accessories: vertical inlet connection, 1-litre siphon with horizontal outlet DN 50 (standard Europe, except CH and UK), 1-litre siphon with horizontal and vertical outlet DN 50 SH 50 (standard Europe, except CH and UK) and outlet DN 40 SH 50 (standard CH)

Order no. 84000.5

TECHNICAL DRAWINGS / S 1 : 20

