

URINALS

Siphonic urinal TAMARO-S90 84010.5



TECHNICAL DATA

Order no.	84010.5
Certified to	DIN 1390, EN 13407
matching for	LIS CU3 Concealed frame for urinal with integrated control, order no. 89266.5
Specification	IR Electronic control for 230 V Concealed power supply
Water inlet	concealed, 1/2"
Outlet	horizontal or vertical
Flushing quantity	minimum 0.7 l - 3.0 l
Flushing capacity	minimum 0.3 l/s
Weight	20,0 kg
Mounting acc. incl.	brass inlet R 1/2", IR electronic
Mounting acc. excl.	Siphon with horizontal outlet, order no. 89497.4 Siphon with vertical outlet and connection bend, order no. 89903.8 Stone screws, order no. 89406.0
Colours	see colour table

SPECIFICATION TEXT

Siphonic urinal Laufen-TAMARO-S90, sanitary ceramic, with control system for net
DIN 1390, EN 13407, dimensions 395 x 360 x 770 mm
minimum 0.7 l - 3.0 l flush, water inlet concealed 1/2",
outlet horizontal or vertical, flushing rate minimum 0.3 l/s
IR electronic control 230 V, concealed power supply, brass inlet R 1/2"
Special feature: Vacuum and performance tested
Further options / accessories: siphon with horizontal outlet, siphon with vertical outlet and connection bend, LIS CU3 concealed frame for urinal with integrated control
Order no. 84010.5

TECHNICAL DRAWINGS / S 1 : 20

