

# URINALS

## Siphonic urinal CAPRINO PLUS

84206.6



### TECHNICAL DATA

Order no.	84206.6
Certified to	EN 13407
Specification	1-l flushing electronic controlled siphonic urinal Electronic control for battery (4x AA 1,5 V) only in combination with fixing set order no. 89280.8
Water inlet	concealed, 1/2"
Outlet	horizontal or vertical
Flushing	1 l
Flushing rate	minimum 0,3 l/s
Weight	20,0 kg
Mounting acc. incl.	Electronic control system battery with all mounting accessories Charge 000 – without fly, 1-litre siphon with horizontal and vertical outlet DN 40 (standard CH) Charge 400 – with fly, 1-litre siphon with hori- zontal and vertical outlet DN 40 (standard CH) Charge 401 – without fly, 1-litre siphon with horizontal and vertical outlet DN 50 (standard Europe, except CH and UK) Charge 411 – with fly, 1-litre siphon with horizontal and vertical outlet DN 50 (standard Europe, except CH and UK)

Mounting acc. incl.	Charge 407 – without fly, 2-litre siphon with horizontal outlet DN 40 (standard UK) Charge 417 – with fly, 2-litre siphon with horizontal outlet DN 40 (standard UK) Wall fixing set M8 LAUFEN, order no. 89280.8
Mounting acc. excl.	Stone screw fixing set M8
Colours	see colour table

### SPECIFICATION TEXT

Siphonic urinal Laufen-CAPRINO PLUS, sanitary ceramic  
electronic control  
EN 13407, dimensions 320 x 350 x 645 mm  
1-l flush, water inlet concealed 1/2", outlet horizontal or vertical, flushing  
rate minimum 0,3 l/s  
electronic control system for battery with all mounting accessories,  
1-litre siphon with horizontal and vertical outlet DN 50 (standard  
Europe, except CH and UK) and outlet DN 40 (standard CH), 2-litre  
siphon with horizontal outlet DN 40 (standard UK)  
Special feature: Vacuum and performance tested  
Further options: Surface refinement LCC (only white), with fly  
Order no. 84206.6

### TECHNICAL DRAWINGS / S 1 : 20

